









Cold Cabinet

CONDENSATE REMOVAL PUMP

A superior stainless steel refrigeration pump built to last. Designed to fit beneath refrigeration units, it pumps away defrost water and filters debris.





225L/h max. flow



35m max. rec. head (flow rate 10L/h)


KEY FEATURES

- Large reservoir
- Stainless steel case
- Plug & play


SUITABILITY

- Single and multiple refrigeration units, OEM
- ✓ Perfect for... Multiple refrigeration units





COLD CABINET @ 230 VAC 50Hz				
Max. flow	225L/h @ 0m head			
Max. rec. head	35m			
Tank capacity	11L			
dB(A) @ 1m	60			
Power supply	230 VAC, 0.38A, 50/60Hz			
Rated	Non continuous			
Class	I appliance			
Max. unit output	n/a			
Max. water temp	40°C / 104°F			
Inlet/outlet	50mm in, 10mm out			
IP Protection	IP21			
Safety switch	3.0A Normally closed			
Thermal protection	✓			
Fully potted	n/a			
Self priming	n/a			



COLD CABINET OPTIONS	
Cold Cabinet – side inlet	FP2120

SUGGESTED XTRA ACCESSORIES				
Description		Part No.		
1 Amp Fuse		FP2620		
Tube To Soil Stack Adaptor	-	FP2038		
Vinyl Tube Braided 3/8" (10mm)		AX5101		



For more installation accessories take a look at our Aspen Xtra range

IN THE BOX

Cold Cabinet pump • 2m Plug & play power cable • 11/2" BSP connector (for 40mm ID waste pipe)* • Install manual

Download manual at aspenpumps.com





Information correct at time of going to press









reliable | silent | simple