

BOMAN . TI DUADBA

MAN + LI UUAUNA

GDMAN · L

5

FULL CATALO

944

FLEXIBLE THERMOPLASTIC HOSES AND FITTINGS FOR HVACR


the preferred flexible choice for all pressure switches, manometers and oil line connections

www.gomax.com

the market leading brand of thermoplastic hose and fittings designed specifically for Air Conditioning and Refrigeration systems



APPLICATIONS



The **QUADRA DN2** flexible thermoplastic capillary hose, in two colors orange and black, represent the most efficient and developed system for the connection of pressure gauges, pressure switches and pressure test points.

Transfer Oil advice the standardization of use of the QUADRA DN2 hose, choosing the orange color for the high pressure circuits and the black color for the low pressure circuits, so identifying in an unambiguous way the two parts of the circuit.

This reduces the possibilities of misconnections of the two pressure lines of the machine during production and maintenance.

The extraordinary number of QUADRA DN2 fittings covers all possible types of installations, making the need of copper rigid tubes and capillaries unnecessary.

QUADRA DN2 hoses and fittings can be easily assembled using the specific QUADRA hand pliers RXA007, or the all new ELECTRIC PLIER RXA011-RXA012.



TECHNICAL DATA

PERFORMANCE and condition of use

				\bigcirc	\bigcirc		R	Å	
non UL part number		part number		DN	OD	BEND Radius	CRIMPING Diameter		
50m	10m	50m	10m	mm	mm	mm		Ø mm	
0780C 0780BC	<mark>0780K</mark> 0780BK	<mark>0380C</mark> 0380BC	<mark>0380K</mark> 0380BK	DN2	6,1	10	7±0,1	NA	7 -0,2 7 +0,1


Car				bar			
	WP			BP		N	Л
bar	MPa	psi	bar	MPa	psi	min °C	max°C
120	12,0	1740	600	60	8700	-45°	+130°

PERMITTED FLUIDS

Type of Gas	Type of Oil
HFC (R134a, R404A, R407A, R407B, R407C, R410A, R507)	polyol ester based
HCFC (R22)	mineral oils
R744	polyol ester based

Classification of QUADRA capillary hoses according to Directive 97/23/CE			
PART NUMBER	CLASSIFICATION		
0780C 0780BC 0780K 0780K 0780BK	paragraph 3 article 3		

Assembly instructions for crimping fittings for QUADRA DN2 capillary hose



Cut the QUADRA capillary hose to the required lenght using the special WXAOO4 cutter Slip the nut over the hose (depending on fitting type). Ensure that the threaded side is pointing towards the end of the hose that needs the assembling.

When pushing the ferrule over the hose end, ensure its correct positioning, in line with the hose end. Push the insert into the hose end you wnat to assemble.

Pay attention not to move the components already fitted and slide the ferrule over the hose towards the insert positioning it in line with the insert. Crimp the ferrule with our hand pliers tupe RXA007, up to the limit stop of the pliers: once the optimal deformation has been achieved the pliers will open automatically.

N


Crimp the ferrule using our pliers cod. RXA010.The deformation is achieved when the plier release. The assembling is finished and the eventual nut can easily slide over the ferrule: check the correct positioning of the componendts and make sure the entire surfaceof the ferrule has been swaged.


Note:

Once the hose has been installed in the system, do not move or rotate it, to avoid unscrewing of the nut or damaging the fitting and the risk of leakage. Do not exceed maximum performance limits. Respect the nut torque value: - Torque wrench 14 7/16"-20 UNF for 1/4" SAE connections | 16 ÷ 18 N·m. Do not exceed 20 N·m - Torque wrench 22 5/8"-18 UNF for 3/8" SAE connections | 30 ÷ 32 N·m. Do not exceed 34 N·m.

 \mathbf{O}

QUADRA DN2 fittings





0

QUADRA CASE

We are glad to introduce our NEW QUADRA CASE. As we are aware that dimensions and comfort matters when we are talking about work, the new QUADRA case is now a briefcase and features a sturdy outer case with a new foam inner divider for the different tools and boxes. Boxes can individually be removed and easily taken to the workstation.

The full case has new part number W00005 and includes more items than before:

- 10 meters of QUADRA DN2 ORANGE HOSE
- 10 meters of QUADRA DN2 BLACK HOSE
- 1 pcs of QUADRA HAND PLIER DN2
- 1 pcs of CUTTER
- 2 pcs of BLADES FOR CUTTER
- 20 pcs of DN2 STRAIGHT FEMALE
- 20 pcs of DN2 STRAIGHT FEMALE WITH VALVE
- 10 pcs of DN2 ELBOW 90° FEMALE 1/4 SAE(7/16 UN) P

The empty case can be ordered with new part number MR293.

- 10 pcs of DN2 "TEE"
- 10 pcs of DN2 "TEE" FITTING WITH 1 FEMALE 1/4 SAE
- 50 pcs of COPPER GASKET 1/4 SAE DN2 -DN4
- 50 pcs of REMOVABLE VALVE OPENER -DN2
- 10 pcs of DN2 MALE 1/4 (7/16-20 UNF)
- 4 pcs of DN2 CROSS FITTING
- 2 pcs of DN2 COPPER BRAZING TUBE MALE
- 5 pcs of DN2 "TEE" FITTING WITH 2 FEMALES 1/4 SAE AT 180°

