







Max Hi-Flow

CONDENSATE REMOVAL PUMP

The best in class Max Hi-Flow tank pump carries on the Aspen Pumps tradition of build quality & high performance. With the lowest dB(A) rating & best IP rating (IP24 splash proof) of any tank pump, the Max Hi-Flow is the quietest & safest pump in its class.



550 L/h max. flow




5m max. rec. head (flow rate 55L/h)



- IP24 Splash proof
- Easy access tank
- Built in spirit level
- Plug & play









✓ Perfect for... Large commercial units








Non-return valve can be cut from 6mm to 10mm (see graphs below)

TANK PUMP OPTIONS

Max Hi-Flow FP3349

MAX HI-FLOW (10)	MM FLOW) @ 230 VAC 50H			
Max. flow	550L/h @ 0m head			
Max. rec. head	5m			
Tank capacity	1.7L			
dB(A)@1m	44			
Power supply	230 VAC, 0.8A, 50Hz			
Rated	Non Continuous			
Class	I appliance			
Max. unit output	733kW / 2.5m Btu/h			
Max. water temp	40°C / 104°F			
Inlets	x4 21-27mm			
Outlets	6mm & 10mm			
IP Protection	IP24			
Safety switch	3A Normally closed			
Thermal protection	✓			



	•		200	LITRES PI	ER HOUR		
METRES HEAD		6mm flov	N				
	6						
	5	٠.		5m	max. reco	ommend	ed head
	4		•				
	3		٠.	٠			
	2				····.	٠	
	1	230 VA	С				٠
	0	50	100	150	200	250	300
				LITRES PI	ER HOUR		





IN THE BOX

Max Hi-Flow tank pump • Plug & Play power cable • Fixing kit incl. rod mount and wall mount clips • Install manual

Download manual at aspenpumps.com

View install video at aspenpumps.com



Fully potted

Self priming



n/a

n/a





